

mm\_trj2pdb  
V.1.0.3

Generated by Doxygen 1.8.5

Fri Aug 30 2013 16:02:48




# Contents

<b>1</b>	<b>mm_trj2pdb</b>	<b>1</b>
1.1	Introduction	1
1.2	How to use	1
<b>2</b>	<b>Install</b>	<b>3</b>
2.1	Requirements	3
2.2	How to install	3
2.2.1	Linux	3
2.2.2	Windows	3
<b>3</b>	<b>Changelog</b>	<b>5</b>
<b>4</b>	<b>File Index</b>	<b>7</b>
4.1	File List	7
<b>5</b>	<b>File Documentation</b>	<b>9</b>
5.1	src/add_main.c File Reference	9
5.1.1	Function Documentation	9
5.1.1.1	error_checking	9
5.1.1.2	print_message	10
5.1.1.3	set_defaults	10
5.2	src/coords.c File Reference	10
5.2.1	Function Documentation	11
5.2.1.1	reading_coords	11
5.3	src/main.c File Reference	11
5.3.1	Function Documentation	12
5.3.1.1	main	12
5.4	src/messages.c File Reference	12
5.4.1	Function Documentation	12
5.4.1.1	message	12
5.5	src/print_struct.c File Reference	12
5.5.1	Function Documentation	13
5.5.1.1	print_structure	13

**Index****14**

# Chapter 1

## mm\_trj2pdb



### 1.1 Introduction

#### About this program:

- Program that creates PDB file from trajectory snapshot

#### Developer:

- Evgeniy Alekseev aka arcanis

<esalexeev (at) gmail (dot) com>

#### License:

- GPL

### 1.2 How to use

#### Usage:

```
mm_trj2pdb -i INPUT -o OUTPUT [ -l LOGFILE ] [ -q ] [ -h ]
```

#### Parameters:

-i	- input file name
-o	- output file name
-l	- log enable
-q	- quiet enable
-h	- show this help and exit



# Chapter 2

## Install

### 2.1 Requirements

The application mm\_trj2pdb requires the following external stuff:

- cmake  $\geq$  2.8
- gcc  $\geq$  4.8

### 2.2 How to install

#### 2.2.1 Linux

```
* mkdir build && cd build
* cmake -DCMAKE_INSTALL_PREFIX=/usr -DCMAKE_BUILD_TYPE=Release ../
* make
* make install
*
```

#### 2.2.2 Windows

```
* create project file using 'cmake'
* compile project
*
```

You may also download compiled executable file for Win\_x86.





## Chapter 3

# Changelog

V.1.0.3 (2013-08-30)

- Bug fixes

V.1.0.1 (2013-07-27)

- initial release



## Chapter 4

# File Index

### 4.1 File List

Here is a list of all files with brief descriptions:

src/ <a href="#">add_main.c</a> . . . . .	9
src/ <a href="#">coords.c</a> . . . . .	10
src/ <a href="#">main.c</a> . . . . .	11
src/ <a href="#">messages.c</a> . . . . .	12
src/ <a href="#">print_struct.c</a> . . . . .	12



## Chapter 5

# File Documentation

### 5.1 src/add\_main.c File Reference

```
#include <stdio.h>
#include "messages.h"
```

#### Functions

- int [error\\_checking](#) (const const char \*input, const char \*output)  
*function that checks errors in input variables*
- int [print\\_message](#) (const int quiet, FILE \*std\_output, const int log, FILE \*f\_log, const int mode, const char \*str)  
*function that prints message in log and stdout*
- int [set\\_defaults](#) (char \*input, int \*log, char \*output, int \*quiet)  
*function that sets default values of variables*

#### 5.1.1 Function Documentation

##### 5.1.1.1 int error\_checking ( const const char \* *input*, const char \* *output* )

function that checks errors in input variables

```
* error\_checking (input, output);
*
```

#### Parameters

<i>aglinp</i>	agglomerate file name
<i>cell</i>	massive of cell size
<i>input</i>	input file name
<i>output</i>	output file name

#### Returns

- 11 - error in 'input'
- 12 - error in 'output'
- 0 - exit without errors

### 5.1.1.2 int print\_message ( const int *quiet*, FILE \* *std\_output*, const int *log*, FILE \* *f\_log*, const int *mode*, const char \* *str* )

function that prints message in log and stdout

```
* print_message (quiet, stdout, log, f_log, 0, str);
*
```

#### Parameters

<i>quiet</i>	status of quiet-mode
<i>std_output</i>	stdout
<i>log</i>	status of log-mode
<i>f_log</i>	log file
<i>mode</i>	number of message in "messages.c"
<i>str</i>	additional text in message

#### Returns

0 - exit without errors

### 5.1.1.3 int set\_defaults ( char \* *input*, int \* *log*, char \* *output*, int \* *quiet* )

function that sets default values of variables

```
* set_defaults (input, &log, output, &quiet);
*
```

#### Parameters

<i>input</i>	mask of trajectory files
<i>log</i>	status of log-mode
<i>output</i>	output file name
<i>quiet</i>	status of quiet-mode

#### Returns

0 - exit without errors

## 5.2 src/coords.c File Reference

```
#include <stdio.h>
#include <stdlib.h>
```

### Functions

- int [reading\\_coords](#) (const int mode, const char \*filename, const int type\_inter, const int \*label\_atom, const float \*cell, int \*num\_mol, int \*num\_atoms, int \*true\_label\_mol, int \*label\_mol, int \*type\_atoms, float \*coords, char \*ch\_type\_atoms)

*function that reads coordinates from special file format*

### 5.2.1 Function Documentation

**5.2.1.1** `int reading_coords ( const int mode, const char * filename, const int type_inter, const int * label_atom, const float * cell, int * num_mol, int * num_atoms, int * true_label_mol, int * label_mol, int * type_atoms, float * coords, char * ch_type_atoms )`

function that reads coordinates from special file format

```
* reading_coords (0, filename, type_inter, label_atom, cell, &num_mol, &num_atoms,
*                 true_label_mol, label_mol, type_atoms, coords, ch_type_atoms);
*
```

#### Parameters

<i>mode</i>	mode of reading; '1' is statgen, '2' is enviro or frad, '3' is agl
<i>filename</i>	input file name
<i>type_inter</i>	number of needed atoms (number of needed molecules)
<i>label_atom</i>	massive of needed atom types (massive of needed molecules)
<i>cell</i>	massive of cell size
<i>num_mol</i>	number of molecules
<i>num_atoms</i>	number of atoms
<i>true_label_mol</i>	massive of true numbers of molecule for atoms
<i>label_mol</i>	massive of numbers of molecule for atoms
<i>type_atoms</i>	massive of atom types
<i>coords</i>	massive of coordinates
<i>ch_type_atoms</i>	massive of char atom types

#### Returns

- 1 - file \$filename does not exist
- 2 - unknown mode
- 0 - exit without errors

#### Work blocks

reading file

translation

free memory

## 5.3 src/main.c File Reference

```
#include <math.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include "add_main.h"
#include "coords.h"
#include "messages.h"
#include "print_struct.h"
```

#### Functions

- int `main` (int argc, char \*argv[])

### 5.3.1 Function Documentation

#### 5.3.1.1 `int main ( int argc, char * argv[] )`

##### Returns

- 1 - error in error\_checking
- 2 - input file does not exist
- 3 - memory error
- 4 - unknown flag
- 0 - exit without errors

## 5.4 `src/messages.c` File Reference

```
#include <stdio.h>
#include <time.h>
```

### Functions

- `int message (const int log, const int mode, const char *text, FILE *output)`  
*function that prints messages to output*

### 5.4.1 Function Documentation

#### 5.4.1.1 `int message ( const int log, const int mode, const char * text, FILE * output )`

function that prints messages to output

```
* message (log, mode, text, output);
*
```

##### Parameters

<i>log</i>	equal to 1 if print to logfile
<i>mode</i>	number of message
<i>text</i>	additional text
<i>output</i>	output file (may be stdout)

##### Returns

- 1 - unknown mode
- 0 - exit without errors

## 5.5 `src/print_struct.c` File Reference

```
#include <stdio.h>
```

### Functions

- `int print_structure (const char *output, const int num_needed_mol, const int *needed_mol, const int num_atoms, const int *label_mol, const char *ch_type_atoms, const float *coords)`  
*function that prints structure to pdb file*



### 5.5.1 Function Documentation

5.5.1.1 `int print_structure ( const char * output, const int num_needed_mol, const int * needed_mol, const int num_atoms, const int * label_mol, const char * ch_type_atoms, const float * coords )`

function that prints structure to pdb file

```
* print_structure (output, num_needed_mol, needed_mol, num_atoms, label_mol,  
*                  char_type_atoms, coords);  
*
```

#### Parameters

<i>output</i>	output file name
<i>num_needed_mol</i>	number of needed molecules
<i>needed_mol</i>	massive of number of needed molecules
<i>num_atoms</i>	number of atoms
<i>label_mol</i>	massive of numbers of molecule for atoms
<i>ch_type_atoms</i>	massive of char atom types
<i>coords</i>	massive of coordinates

#### Returns

0 - exit without errors

# Index

- add\_main.c
  - error\_checking, [9](#)
  - print\_message, [9](#)
  - set\_defaults, [10](#)
- coords.c
  - reading\_coords, [11](#)
- error\_checking
  - add\_main.c, [9](#)
- main
  - main.c, [12](#)
- main.c
  - main, [12](#)
- message
  - messages.c, [12](#)
- messages.c
  - message, [12](#)
- print\_message
  - add\_main.c, [9](#)
- print\_struct.c
  - print\_structure, [13](#)
- print\_structure
  - print\_struct.c, [13](#)
- reading\_coords
  - coords.c, [11](#)
- set\_defaults
  - add\_main.c, [10](#)
- src/add\_main.c, [9](#)
- src/coords.c, [10](#)
- src/main.c, [11](#)
- src/messages.c, [12](#)
- src/print\_struct.c, [12](#)